



### Specifications

<b>MODEL</b>	XP-3204T			
<b>Print Head Technology</b>	DOD Piezo Electric Technology			
<b>No. of Print Head</b>	12 Heads(3 Heads/Color)			
<b>Print Mode</b>	Uni/Bi-direction			
<b>Color</b>	4 colors (C,M,Y,K)			
<b>Ink Type</b>	Solvent based pigment			
<b>Resolution &amp; Max. Print Speed</b>	D6Pass	4Pass	6Pass	F4Pass
	200x1110dpi	300x740dpi	300x1110dpi	600x740dpi
	25sqm/h	23sqm/h	16sqm/h	12sqm/h
<b>Media</b>	Roll and Sheet			
<b>Max. Printing Width</b>	3,290mm			
<b>Max. Media Width</b>	3,310mm			
<b>Dimensions(W x D x H)</b>	4,600 x 1,025 x 1,700mm			
<b>Weight</b>	800kg			
<b>CPU</b>	32BIT RISC			
<b>Memory</b>	256MB			
<b>Command Language</b>	SP-RTL & HP-RTL Emulation			
<b>Interface</b>	TCP/IP			
<b>Input Voltage</b>	Printer : Free Voltage(85~265 VAC) / Heater : 220V			
<b>Motor Type</b>	Carriage : AC Servo Motor / Feed : AC Servo Motor			
<b>Media Type</b>	Flex,Banner Flex,Sheet,etc			
<b>Other Features</b>	Adjustable Fire Voltage System			
	Auto Ink Supply System			
	Auto Heating System & Dry Fan			
	Auto Feeding System			
	Calibration Control			
	Speed Control(Head Carriage / Feed)			
	Auto Media Check System			
Cover Open Check				