



LIPI MARKETING PVT. LTD.

Follow Us at
f Instagram G+ Twitter YouTube



Hi-Speed, Hi-Res UV Flatbed Printer

F 25UV



Features:

- ▶ Grayscale Printhead, Supporting 4-level Grayscale Printing
- ▶ Standard Printing **Speed Up To 80sqm/hr**, Printing Size Max 100*51 Inch
- ▶ Hi-precision Vacuum Platform With Sectional Zones To Fit Media In Different Sizes
- ▶ Supporting Multi-layer Printing, Including White And Varnish Printing **C-W-C, W-C-V Modes**
- ▶ Wide Applications In Glass, Acrylic, Wallpaper, Wood Panel, Any Rigid Board Surface Printing

Contact us:

LIPI MARKETING PVT. LTD.

No: 28, 3rd Cross St, Venkateswara Colony,
Nehru Nagar, Kottivakkam, Chennai, Tamil Nadu 600041

+9194443 95477 / +91 94443 95467

✉ sales@lipimarketing.com



www.lipimarketing.com

Standard Features

1. 4 rows printheads array, white color supported

F25UV supports standard 4 color printing max 12 print heads. white and varnish are optional to Extend color configuration and applications.

2. Printhead Anti-crash function

Anti-crash function guarantees the carriage will stop in the case of printhead lower than substrates To protect printhead from mis-operation or inferior materials

3. Substrate Thickness Automatic detection, Printhead Height Adjustment


F25UV Supports printing over material as thick as 100mm. The System Automatically detects Material Thickness, and Adjusts printhead Height It Improves production automation and Image Output Quality to a large extent

4. Auto rise-and-fall substrate locator System

F25UV Supports Automatic substrate location to guarantee printing precision on rigid board

5. Anti-Static bar

Reducing the ink over-spray caused by static and improving the print quality on some substrates



Standard Features

6. White Ink Re-circulation System

F25UV Printer Offer Eight Major utilizing White in application white ink re-circulation result in an Effective of Ink Starvation an Protects print heads from clogging hazard

7. Dual Negative Pressure System

Negative Pressure Automatic Adjustment free of manual Operation Stable and smarter. Independent white and varnish negative pressure system can avoid white and varnish Ink dripping Problem caused by negative pressure sharing. White ink and Varnish are more fluent

8. Unique 3-Layers Printer Function

F25UV Digital printer Supports Unique 3-layers function and C-W-V Printing at one Printing. All Printing in one Job

9. Approved By Eu and International Standard System

Conforming to ISO9001, 2008 International Standard Sytem, CE, FCC, ULCE and RoHs Certificates Obtained



Technical Parameter

Model	F25 Flatbed Printer	
Printhead	3-Row 9 Heads, Ricoh G5/G6 (linear motor for option)	
Printing Speed	3-RoW 10H G6	58 sqm/hr
	4-RoW 12H G6	80 sqm/hr
	3-RoW 14H 1024A	86 sqm/hr
Resolution	Up to 2400dpi	
Printhead Technology	Piezoelectric Inkjet, UV LED Curing, Grayscale Technology	
Ink Type	LED UV Inks	
Color	Max 8 Colors (for option) CMYK + Lc + LM+W+V white and varnish printing supported	
Cartridge Capacity	1.5 Liter/Color, Automatic Monitoring Ink volume, Low ink alarming	
RIP Software	Photprint Server Flora, Onyx12, Caldera 12 compatible	
Color management	Icc based color, adjustment curves, density adjustment	
File Format	TIFF, JPEG, Postscript, EPS, PDF, etc...	
Media		
Handling	High-precision Vacuum platform is applied to rigid panels. Media locating pin, anti-below function for option	
Media Size	2.54 x 1.30m	
Media Weight	50kg/m ²	
Media Type	Wood board, Aluminum board, door plank, paper board, PVC, Ceiling, Glass, Acrylic, Fabric, etc...	
Data Transfer		
Interface	USB3.0	
UV Curing System	LED UV Lamp, Energy-saving, environment friendly curing solution And long working life. Every single LED light power can be Adjusted to Meet Different material requests.	
Dimension & Weight		
Printer	5100 x 2100 x 1580mm	
Package	5260 x 2280 x 1860mm	
Weight	1900kg	
Operating Conditions		
Temperature	20° to 30°C	
Humidity	40-80%(non-condensing)	
Electricity Requirements		
Power	System: 2650W; Chiller, Suction motor: 4500W	
Requirements	200-240V AC, Single Phase, 50/60Hz, 32A(printer)	



LIPi MARKETING PVT. LTD.

No: 28, 3rd Cross St, Venkateswara Colony,
Nehru Nagar, Kottivakkam, Chennai, Tamil Nadu 600041

+91 94443 95477 / +91 94443 95467 ✉ sales@lipimarketing.com



www.lipimarketing.com