




LIPI MARKETING PVT. LTD

Follow Us at
f i G+ t y

KENJET

KG - DS 1602 C M Y K

Sublimation Printer




360 x 2400dpi 4 Pass 43 sqm/h

720 x 1800dpi 6 Pass 30 sqm/h

720 x 2400dpi 8 Pass 21 sqm/h



Both Sublimations and direct to textile printer are examples of our expertise and engineering: Top Perform ant, Reliable and Precise. With **Kenjet Series** Printer you can Maximize Production While controlling Quality and Minimizing costs for beautiful soft signage apparel and interior decor Item that will set your business apart From the competition. Wide application in clothing, home decoration Fabrics, Sampling, Shirt, and Canvas bags, Bolster Scooter, Flags, Textile Gadgets etc...




CONTACT US:


+9194443 95467 / +91 94443 95477

www.lipimarketing.com

Main Parts & Features




Heating of the Printer Carriage bottom plate to Effectively Improve printing Stability



Head cleaning and moisturizing Makes operation and maintenance more convenient



High Quality DC Servo motor Good Stability and long life



Three-Foor Pinch Roller Structure Bring more Stable Feeding Accuracy

Stable 3L Bulk System Ensures Amazing Printing Speed




Built-in Infrared Heater and cooling Fan to accelerate the Drying of the media



External Infrared Drying System



External Power Supply Intelligent Rolling System



Technical Parameter

Printing Head		Two i3200-A1 Print Head
Printing Technology		Piezoelectric Inkjet
Acceptable Media	Width	210 - 1650mm
	Thickness	Maximum 39.3mil (1mm)
	Weight	60Kg
Printing Width		210 - 1600mm
Ink Cartridge	Type	Dye Sublimation Ink
	Capacity	Continual Ink Supply System (1.5L Ink Tank)
	Color	4 Colors (CMYK)
Printing Resolution		Maximum 2400dpi
Printing Speed	4 Pass	43 sqm/h
	6 Pass	30 sqm/h
	8 Pass	21 sqm/h
Media Heating System		Integrated post heater & Infrared Dryer & Fan System
Interface		Ethernet Interface
Power		7500W
Power Supply		AC 220V \pm 10%, 50/60 Hz
Dimension with stand		3010 x 1048 x 1420mm (W x D x H)
Weight with stand		300Kg
Package Dimensions		3140 x 1048 x 1490mm (W x D x H)
Package Weight		350Kg
Environment	Power on	Temperature: 15°C to 32°C Humidity: 35% to 80% (no condensation)
	Power off	Temperature: 5°C to 40°C Humidity: 20% to 80% (no condensation)



LIPi MARKETING PVT. LTD

No: 28, 3rd Cross St, Venkateswara Colony, Nehru Nagar, Kottivakkam, Chennai - 600041

+9194443 95467 / +91 94443 95477

sales@lipimarketing.com www.lipimarketing.com