



LIPI MARKETING PVT. LTD

Follow Us at
f Instagram G+ Twitter YouTube




T-Shirt Digital Heat Transfer Systems

KG - DTF 6002 C M Y K + W



► Head Configure & Speed



Two i3200 Heads

Two i3200 Heads


360 x 1800dpi - 4 pass	10m ² /h
720 x 1200dpi - 6 pass	7m ² /h
720 x 1800dpi - 8 pass	4m ² /h

CONTACT US


+91 94443 95467 / +91 94443 95477

www.lipimarketing.com

► Special Features




Imported mute Guide Rail,
Low Noise and High Precision



High-performance take up device,
Suitable for various media




Simple control switch,
Simple operation & Easy to use




THK High-precision
Mute rail



Stable bulk system ensures
Amazing printing speed



Carriage anti-collision device,
Protect the print head



Efficient powder Shaking device,
Powder shaking is clean



External power supply,
Intelligent rolling system

► Working Process



► Shaking Powder & Colour Fix Machine

Model	KG - DTF 6002
Media Width	0-600mm
Applicable Media	Nylon, Chemical Fiber, Cotton, Leather, Swimwear, Wetsuit, PVC, EVA, etc...
Powder Control	Powder shake control, Powder control, Powder direction and volume control
Heating & Drying Function	Multi-stage heating system, Drying, Cold air fan function
Rewind Function	Automatic induction winding
Electrical Parameter	Rated Voltage: 220V Rated Current: 20A
	Rated Power: 3.42kW Power Consumption: 1kW - 2.5kW
Machine Size	2023 x 1210 x 1337mm
Machine Weight	180kg

► Technical Parameter

Model		KG - DTF 6002
Print Head		Double i3200 Print Head
Printing Technology		Piezoelectric Inkjet
Acceptable Media	Width	620mm
	Thickness	1 mm
Printing Width		620mm
Ink Cartridges	Type	Transfer Pigment Ink
	Capacity	Continual Ink Supply System (220ML)
	Colour	CMYK+ W
Speed	4 Pass	(360 x 1800dpi) - 10m ² /h
	6 Pass	(720 x 1200dpi) - 7m ² /h
Applicable Media		Transfer Film
Colour Manage		ICC or Density Curve
Meda Heating System		Powder & Colour Fixing Machine
Interface		RJ-45 /LAN
RIP Software		Main top
Power Supply		50Hz / 60Hz, 220V/110V / 10A
Environment	Temperature	10℃ to 38℃
	Humidity	40% to 70%
Printer Size		1620 x 620 x 1280mm (L x W x H)
Weight		110kg



LIPi[®] LIPI MARKETING PVT. LTD

#11,K.P.N Colony, 6th Street, Tiruppur, India-Pin: 641 601

☎ +9194443 95467 / +91 94443 95477

✉ sales@lipimarketing.com 🌐 www.lipimarketing.com