



LIPI MARKETING PVT. LTD.

Follow Us at




KENJET

Eco Solvent Printer


KG - ES 3200



Two - Dx5 Head



Two i3200 Heads



Application



CONTACT US


+91 94443 95467 / +91 94443 95477

www.lipimarketing.com


Major Parts & Technical Parameter



THK High - Precision Mute Rail



New Pinch roller Structure of three in group brings more stable feeding precision



High - Precision and High - Stability Tensioning Pulley System




High Quality DC Servo Motor with Good Stability and long life




The Automatic Cleaning Assembly adds a Single-way Valve to Increase the Stability of the ink supply



Infrared Heater and Cooling Fan



Automatic moisturizing cleaning Assembly ensures the stability of head cleaning and improve working stability



External Power Supply, Intelligent Rolling System

Model		KG - ES 3200	
Print Head		2- Dx5 Print Heads	2- i3200 Print Heads
Printing Technology		Piezoelectric Inkjet	
Media	Width	3250mm	
	Thickness	1.5mm	
	Weight	80kg	
Printing Width		3200mm	
Ink Cartridges	Type	Eco Solvent Ink	
	Capacity	220ml Ink Cartridge with 1.5L Ink Tank	
	Colour	4 Colour (6, 8 Colour Optional)	
Printing Resolution		Maximum 1440 dpi	
Printing Speed	4 Pass	33 sqm/h	62 sqm/h
	6 Pass	26 sqm/h	47 sqm/h
	8 Pass	18 sqm/h	31 sqm/h
Media Heating System		Intergrated Post Heater & Infrared Dryer & Fan System	
Interface		USB 2.0	
Power Supply		AC 220 ± 10%, 50/60Hz	
Dimensions		4580 x 970 x 1580mm	
Weight		1000kg	
Environment	Power On	Temperature: 15°C to 32°C Humidity: 35 to 80% (no condensation)	
	Power Off	Temperature: 5°C to 40°C Humidity: 20 to 80% (no condensation)	



LIPi MARKETING PVT. LTD

No: 28, 3rd Cross St, Venkateswara Colony, Nehru Nagar, Kottivakkam, Chennai - 600041

+9194443 95467 / +91 94443 95477

sales@lipimarketing.com www.lipimarketing.com