





IPI MARKETING PVT. LTD.





Roll to Roll UV 3.2M

Superior Performance

- Whole Frame Construction, Integrated Vacuum Platform (Special Purpose on Faltbed) Platfrom Plane Resolution within 0.33M. All make sure High Quality printing after long distance delivery
- Integrated High Resolution steel beam and match with imported rail to make sure high stand 5M printing
- Ink Alarm device, Double Negative Control to Guarantee Continues and Stable ink supply
- More Configuration Choices: 2Head, 4Head, 5Head and 8Head are Optional 6colors, 8colors, CMYK White CMYK, CMYK White Varnish or more
- 5M printing without bonding Especially for high Level Printing
- New State of Color Process Technology, Perfect Backlit the Ink will be saved 30%
- Environment Friendly: Ink Contain VOC free (Volatile Organic Gas)

Accessory Details



Panasonic Motor



Automatic Integrated Control panel



Ink Alarm Device





Integrated Vacuum Platform



Double THK Guide Rail

Technical Parameter

Color		СМҮК		
Print Head & No of Head		8 KM1024i	12 KM1024i	16 KM1024i
Print Mode & Speed	Draft 3 Pass	78m²/h	88m ² /h	117m ² /h
	Standard 4 Pass	60m²/h	75m ² /h	90m²/h
	High Quality 6 Pass	45m³/h	55m ² /h	66m²/h
Printing Media		Soft Roll to Roll		
Printing Width		3200mm		
Drying System		UV-LED Curing		
Image File Format		TIFF, JPEG, EPS, PDF		
RIP Software		Photoprint / PrintFactory, ONYX (Optional)\		
Ink Type		UV- Ink		
Ink Volume		2000ml Volume Ink, Automatic Ink Detector and Ink Supply System		
Power Supply		AC 220V		
Dimension		5656 x 1390 x 1715mm (L x W x H)		
Packing		5790 x 1520 x 1895mm (L x W x H)		
Net Weight		3200Kg		
Gross Weight		3300Kg		
Working Ennviroment		Temperature: 15-300C Humidity 40-80%RH		
Power		6kW		

Application











Canvas Reflective Stickers

Soft Film

